

## SPRAY WASH CABINETS

*Wash in three easy steps—*

- 1. Parts are loaded, wash cycle timer is set.*
- 2. Turntable rotates, blasting parts from all angles with hot soap and water solution.*
- 3. Cleaned parts are unloaded and dry in seconds.*

**Two Sizes  
Available**



SWC-  
STANDARD  
shown

### Features:

- ◆ 14 gauge steel construction
- ◆ Large octagonal door for maximum turntable access
- ◆ Multi-directional spray
- ◆ Easily removable parts tree and hanging small parts basket
- ◆ Tank drain for sludge removal
- ◆ Jam free turntable
- ◆ Filter basket with removable screen
- ◆ Timer and safety door switch
- ◆ Oil skimmer
- ◆ Casters for mobility
- ◆ **FREE SOAP**

### SPECIFICATIONS

	SWC-STANDARD	SWC-TRUCK
Interior height	43"	54"
Interior width	32"	32"
Turntable diameter	30"	30"
Overall height	66"	78"
Floor space required	44" x 43"	44" x 43"
Load capacity	500 lbs.	500 lbs.
Cycle time	60 min. spring wound timer	
Motor	1 hp	2 hp
Pump output	50 gpm	92 gpm
Spray jets	18	22
Heater	4 ½ kw	4 ½ kw
Solution capacity	50 gals	50 gals
Filter area (screen)	170 sq. in	170 sq. in
Electrical requirements	208-240/60/1	208-240/60/1
Shipping weight	500 lbs.	700 lbs.