

SPRAY WASH CABINETS

Wash in three easy steps—

1. Parts are loaded, wash cycle timer is set.
2. Turntable rotates, blasting parts from all angles with hot soap and water solution.
3. Cleaned parts are unloaded and dry in seconds.

Two Sizes Available



SWC-STANDARD shown

Features:

- ◆ 14 gauge steel construction
- ◆ Large octagonal door for maximum turntable access
- ◆ Multi-directional spray
- ◆ Easily removable parts tree and hanging small parts basket
- ◆ Tank drain for sludge removal
- ◆ Jam free turntable
- ◆ Filter basket with removable screen
- ◆ Timer and safety door switch
- ◆ Oil skimmer
- ◆ Casters for mobility
- ◆ **FREE SOAP**

SPECIFICATIONS

	SWC-STANDARD	SWC-TRUCK
Interior height	43"	54"
Interior width	32"	32"
Turntable diameter	30"	30"
Overall height	66"	78"
Floor space required	44" x 43"	44" x 43"
Load capacity	500 lbs.	500 lbs.
Cycle time	60 min. spring wound timer	
Motor	1 hp	2 hp
Pump output	50 gpm	92 gpm
Spray jets	18	22
Heater	4 ½ kw	4 ½ kw
Solution capacity	50 gals	50 gals
Filter area (screen)	170 sq. in	170 sq. in
Electrical requirements	208-240/60/1	208-240/60/1
Shipping weight	500 lbs.	700 lbs.